







Tecle Polipasto Prowinch c/carro electrico Monoviga 6.3 Tons trifasico

Especificaciones Técnicas

Capacidad de Carga	6000 kg / 13 889 lb	Altura de Izaje Estandar (Customizable)	40 ft / 12 m
Velocidad /min	2.62 - 16.4 ft/min / 0.8 - 5 m /min	Numero de Velocidades	2 Speed
Voltaje	3 Phase 208~240/480V 50/60Hz	Clase de Servicio	H4/M5/2m/Class D
Tipo de Motor	Squirrel Cage Induction Motor	AMP Motor	12.7 A (@ 380v)
RPM Motor	2930 / 470 rpm (@50hz)	Freno Motor	Sew Eurodrive BE5 Electromagnetic Release Brake >125%
Grado de Aislacion	F	Protección IEC Motor	IP55
Protección Tablero de Control	IP65	Freno Dinámico	Included
Control	Pendant Control and Remote Control Telecontrol F24-6D	Voltaje del Control	48V
Marca Motor de Izaje	Sew Eurodrive DRS132M12	Reductor de Izaje	Sew Eurodrive G77
Tipo Transmisión / Reductor	Sew Eurodrive G77	Relación de Transmisión	87.32
Cable	Ø 8.8 mm K19S IWRC 2160	Humedad	<85%
Temperatura	-4°~104° F / -20°~40° C	Reductor Carro	SEW Eurodrive RF17
Motor Carro	SEW Eurodrive DRN71M4	Potencia del Trolley	0.37 ~ 0.64 kW
Nivel de Ruido	82 dB	Velocidad del Trolley /min	16 ~ 65 ft/min. / 5 ~ 20 m/min
Cantidad de Velocidades	2	Rango de ancho de la Viga	7.9~13.7 in / 200~350 mm
Normas	ASME HST-4 , ASME B30.16 , B30.17 , EN14492-2 , EN60204-32	Garantía	3 Year
Hoist Contactor Brand	Schneider or EATON		



DRIVE TECHNOLOGY

SEW Eurodrive high performance Motor, reducer and brake. Compact design, light weight, low energy consumption, low noise and eco-friendly design. Electromagnetic brake disc (Asbestos-free). Long Service life and easy maintenance.



OVERLOAD PROTECTION

Load Cell connected to a Limit Relay (Adjustable) to avoid overloading of the hoist.



WIRE ROPE GUIDE

Helps the winding of the rope on the drum. Light weight and highly resistance. Design to reduce friction on the wire rope and avoid premature wear.



HIGH-PERFORMANCE WIRE ROPES

High-performance wire rope with tensile strength up to 2160Mpa. Galvanized surface and high flexibility to ensure long service life.



DRUM

Q345 steel, seamless grooved drum. Design to fulfill FEM and ASME standards and ensure a safe operation.



LIMIT SWITCHES

High precision adjustable height limit switches, for all movements of hoist and trolley.



LIFTING HOOK GROUP

DIN standard lifting hook with safety clasp. Forged by the high-strength material of T grade.



CONTROL BOX

Electric Control box with Schneider Inverter, Eaton contactors and components. Compact design, easy access, IP65 Enclosure.

Detalles del Empaque

H Altura Muerta	23.46
A Altura Total	33.31
X Diametro Rueda	3.94

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso