




Tecle Cadena - Neumatico Anti explosion de 1,5 Tons - Nickel kit

Características Esenciales

- 1.5 Ton Pneumatic Chain Hoist - Heavy Duty - Explosion Proof - Nickel Kit
- Nickel Coated: Chain hook, bottom block, Sprocket, Load sleeve, Safety Catch
- Includes: Overload Protection - Slip Clutch / Failsafe Automatic Internal Break / Pendant Control with emergency stop / Chain containers
- Meets and exceeds ASME B30.16 / HST-5 standards / Load Test at 130% SWL / ATEX Directive

Especificaciones Técnicas

Capacidad de Carga	1.5 Ton	Altura de Izaje Estandar (Customizable)	20 ft / 6 m
Numero de Velocidades	1 Speed	Protección Antiexplosión	- EX 2 GD IIA T4 EX 2 GD IIB T4 EX 2 GD IIC T4 ZONES 1, 2 AND 21, 22 - Nickel Coated: Chain hook, bottom block, Sprocket, Load sleeve, Safety Catch
Clase de Servicio	100% Duty Cycle	Freno Motor	>125% WLL Automatic self-adjusting multidisc Brake
Control	Pendant Control w/emergency stop	Tipo Transmisión / Reductor	Epicycle Gearbox (Grease Filled and Sealed)
Tipo de Cadena	G80 RUD Germany 5:1 Safety Factor	Dimensiones de la Cadena	9 x 27 mm
Caidas de Cadena	1	Temperatura	-20°C to 70°C
Nivel de Ruido	83 dBA @ 1m	Normas	ASME B30.11 / B30.16 / HST-5 DIN EN818-7 SANS 1638 compliant ATEX EX Classification according to EC Directive on Hazardous Locations 94/9/EEC
Fabricado en	South Africa	Garantía	3 Year
Pendant Control Yes No	Included	IEC Pendant Control Protection	IP66
Pendant Control Emergency Stop	Yes		



Dimensions in mm / Dimensiones en mm

Detalles del Empaque

H Altura Muerta	14.21
D Depth	5.62
W Ancho	15.11
J Boca Gancho	0.98

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso