



**1 ton Electric Chain Hoist 2 Speed
575V 3Ø 50/60HZ**

Especificaciones Técnicas

| | | | |
|----------------------------------------------------------|--------------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------|
| Capacidad de Carga | 1 ton | Altura de Izaje Estandar (Customizable) | 20 ft / 6 m |
| Velocidad /min | 1 st speed : (7.8 ft @60Hz - 2 mt @50Hz) / 2 nd speed : (42.6 ft @60Hz - 6.5 mt @50Hz) | Numero de Velocidades | 2 Speed |
| Voltaje | 3 Phase 575v 50/60 Hz | Clase de Servicio | H4/M5/2m/Class D |
| Protección IEC Motor | IP55 | Control | Pendant Control IP66 |
| Voltaje del Control | 24V | Tipo Transmisión / Reductor | Spur gearbox |
| Tipo de Cadena | G100 Nickel | Dimensiones de la Cadena | 7.1 mm |
| Caidas de Cadena | 1 | Longitud de cadena | 20 |
| Humedad | 20%~90% | Temperatura | -4 ~ 104° F / -20 ~ 40° C |
| Normas | ASME HST-1 , ASME B30.16 , EN60204-33 | Garantía | 3 Year |
| Hoist Contactors Amps | 18A | Hoist Contactor Brand | Schneider |
| Hoist Contactor Model | LC1D18B7C / LC1D188B7C | Hoist Contactor Coil Voltage | 24 V |
| IEC Hoist IP Protection | IP55 | Pendant Control Yes No | Yes |
| IEC Pendant Control Protection | IP66 | Pendant Control Emergency Stop | Yes |
| Pendant Control total Length | 17 ft | Hoist Motor Power in KW | 1.5 |
| Hoist Motor Brake Type and DC Voltage | DC260V | Overload Protection | Overload Motor Clutch |
| Hour Meter | Internal Working Hour Meter | Brake rectifiers-half-wave | PWRX-BKTF-HW |
| Hoist Motor Insulation Grade | F | Recommended Hoist Protection Circuit Breaker AMPs and Type | Type D 2A at 575V |
| Optional Load Chain Brand & Country of Origin | FEC Japan | Reducer Lubrication Type | Oil |
| Paint Specifications | Electrostatic Sprayed Plastic (ESP) Epoxy resins, Polyester Resins, Barium, Pigments | Load Chain weight per foot [lbs] | 0.74 |
| 1st Package Type | Wood Crate | | |



[Size list: mm]

| Rated load (t) | Type | Minimum distance between hooks: H | A | B | D | E | I | M | N | K | L |
|----------------|-----------|-----------------------------------|-----|-----|-----|-----|----|----|----|----|----|
| 1 | PWRXF1-01 | 455 | 590 | 276 | 330 | 210 | 32 | 16 | 25 | 42 | 32 |
| 2 | PWRXF2-01 | 550 | 590 | 276 | 330 | 210 | 38 | 20 | 35 | 52 | 42 |
| 3 | PWRXF3-01 | 560 | 695 | 350 | 420 | 265 | 45 | 20 | 34 | 59 | 48 |
| 5 | PWRXF5-02 | 675 | 695 | 350 | 420 | 307 | 55 | 28 | 44 | 60 | 48 |

Peso & Dimensiones

| | | | |
|-------------------|-----------------|----------------------------------------|--------|
| Peso Total | 209 lbs / 95 Kg | H Altura Muerta | 20.31 |
| | | A Altura Total | 17.91 |
| | | D Depth | 23.23 |
| | | W Ancho | 12.99 |
| | | J Boca Gancho | 1.65 |
| | | Peso Total (sin cable o cadena) | 113.22 |

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso