

2200 lb Mini Pro-C Electric 13 ft Chain Hoist Milwaukee M18 x 2 Battery Powered Double Brake H3 Duty 16000 FLC



Especificaciones Técnicas

Battery	Not Included	Full Load Duty Cycles	32000
Hoist Limit Switches	Up and Down	Power Battery Model	2 x Milwaukee M18 (Not Included)
Power Battery Voltage	18V x 2 Tot. 36V	Power Battery Location	Pendant Control and/or Hoist Housing
Pendant Control w/Quick Connector	Yes	Capacidad de Carga	1 t / 2200 lb
Altura de Izaje Estandar (Customizable)	13 ft / 4 m	Velocidad /min	planning up/down 9.85 ft/min
Numero de Velocidades	1 Speed	Voltaje	Milwaukee 18V x 2 = 36V
Clase de Servicio	A2 ED 40% / H3 / M4	Tipo de Motor	Brushless motor
RPM Motor	12500	Freno Motor	Yes
Grado de Aislacion	B	Protección IEC Motor	IP54
Protección Tablero de Control	IP23	Control	Wireless Included. Pendant Optional
Freno al Reductor	Yes	Tipo de Cadena	7 X 21 mm G100
Caidas de Cadena	1	Normas	ASME/ANSI B30.16
Garantía	3 Year	IEC Pendant Control Protection	IP23
Pendant Control total Length	Optional	Wireless Control Yes No	PWYT-W-SET-2C-BM
Hoist Motor Brake Type and DC Voltage	Electronic brake and Mechanical brake	Standards Certified	TÜV Rheinland: EN ISO 12100:2010, EN ISO 12100:2010, EN 60204-32:2008, AfPS GS 2019:01 PAK

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso